



**MLU80V-T/MLU80V-T1/  
MLU150V-T/MLU150V-T1/MLU200V-T/MLU200V-T1**  
80-200W, CONSTANT VOLTAGE TRIAC & ELV EDGE DIMMABLE LED DRIVER

- Flicker-free for whole dimming range
- 12/24Vdc constant voltage
- Match up with most of Triac & ELV dimmers in America
- Protection: short circuit / over temperature/ over voltage
- Derating current for over high ambient temperature
- Dimming level memory at mains restores
- 5 year warranty



MLU80V-T/MLU80V-T1

MLU150V-T/MLU150V-T1/  
MLU200V-T/MLU200V-T1



unit:mm

**SPECIFICATIONS**

Model	MLU80V-T	MLU80V-T1	MLU150V-T	MLU150V-T1	MLU200V-T	MLU200V-T1
Dim Interface	Triac & ELV	Triac & ELV	Triac & ELV	Triac & ELV	Triac & ELV	Triac & ELV
Dimming Range	5%-100%	5%-100%	5%-100%	5%-100%	5%-100%	5%-100%
Input Voltage	120Vac	120Vac	120Vac	120Vac	120Vac	120Vac
Efficiency	82%	82%Max. @120Vac	85%	85%	85%	85%
Output current/ voltage & load	12Vdc, 6.67A Max.	24Vdc, 3.33A Max.	12Vdc, 12.5A Max.	24Vdc, 6.25A Max.	12Vdc, 16.67A Max.	24Vdc, 8.33A Max.
Safety standard	UL 8750	UL 8750	UL 8750	UL 8750	UL 8750	UL 8750
Certification	UL(Pending)	UL(Pending)	UL(Pending)	UL(Pending)	UL(Pending)	UL(Pending)
Operation Temp.	-25°C ~50°C	-25°C ~50°C	-25°C ~50°C	-25°C ~50°C	-25°C ~50°C	-25°C ~50°C
IP rating	IP65	IP65	IP65	IP65	IP65	IP65


**MLU80V-D/MLU80V-D1/  
MLU150V-D/MLU150V-D1/MLU200V-D/MLU200V-D1**  
80-200W, CONSTANT VOLTAGE LEADING & TRAILING EDGE DIMMABLE LED DRIVER

- Flicker-free for whole dimming range
- 12/24Vdc constant voltage
- Built-in DALI interface
- Protection: short circuit / over temperature/ over voltage
- Derating current for over high ambient temperature
- Dimming level memory at mains restores
- 5 year warranty



MLU80V-D/MLU80V-D1

MLU150V-D/MLU150V-D1/  
MLU200V-D/MLU200V-D1



unit:mm

**SPECIFICATIONS**

Model	MLU80V-D	MLU80V-D1	MLU150V-D	MLU150V-D1	MLU200V-D	MLU200V-D1
Dim Interface	DALI	DALI	DALI	DALI	DALI	DALI
Dimming Range	0%-100%	0%-100%	0%-100%	0%-100%	0%-100%	0%-100%
Input Voltage	120Vac	120Vac	120Vac	120Vac	120Vac	120Vac
Efficiency	82%	82%Max. @120Vac	85%	85%	85%	85%
Output current/ voltage & load	12Vdc, 6.67A Max.	24Vdc, 3.33A Max.	12Vdc, 12.5A Max.	24Vdc, 6.25A Max.	12Vdc, 16.67A Max.	24Vdc, 8.33A Max.
Safety standard	UL 8750	UL 8750	UL 8750	UL 8750	UL 8750	UL 8750
DALI standard	IEC62386-102, IEC62386-207	IEC62386-102, IEC62386-207	IEC62386-102, IEC62386-207	IEC62386-102, IEC62386-207	IEC62386-102, IEC62386-207	IEC62386-102, IEC62386-207
Certification	UL(Pending)	UL(Pending)	UL(Pending)	UL(Pending)	UL(Pending)	UL(Pending)
Operation Temp.	-25°C ~50°C	-25°C ~50°C	-25°C ~50°C	-25°C ~50°C	-25°C ~50°C	-25°C ~50°C
IP rating	IP65	IP65	IP65	IP65	IP65	IP65

American Dimmable LED Drivers

American Dimmable LED Drivers

